



TECHNICAL DATA

Product Spec Sheet - Standard Excelon Imperial Texture

Form(s):
Tile

12 in (305 mm) Wide x 12 in (305 mm) Length

Gauges:

1/8 in (3.2 mm) overall (nominal)

3/32 in (2.4 mm) overall (nominal)

Reference Specs:

ASTM F 1066 Class 2 - through-pattern

Durability :

1/8 in (3.2 mm) - Very Good

3/32 in (2.4 mm) - Good

Fire Test Data :

ASTM E 648 Critical Radiant Flux Class I - 0.45 or more watts/cm²

Maintainability :

1/8 in (3.2 mm) - Good

3/32 in (2.4 mm) - Good

ASTM E 662 Smoke Developed 450 or less
Numerical flammability ratings alone may not define the performance of the product under actual fire conditions. These ratings are provided only for use in the selection of products to meet the specified limits.

Resilience :

1/8 in (3.2 mm) - Good

3/32 in (2.4 mm) - Good

Static Load Limit:

ASTM F 970 125 psi (8.8 kg/cm²)

Approximate Installed Cost (per Sq. Ft.):
Tile

1/8 in(3.2 mm): U.S.: \$1.75 to \$2.25

3/32 in(2.4 mm): U.S.: \$1.75 to \$2.25

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.