

**MANUFACTURING
SPECS**

	US	METRIC
CONSTRUCTION	Through-Pattern Vinyl Composition Tile	
SIZE	12" x 12"	304.8 mm x 304.8 mm
WEARLAYER THICKNESS	.125 inches	3.18 mm
OVERALL THICKNESS	.125 inches	3.18 mm
PACKAGE COUNT	45 / ctn	
AVERAGE WEIGHT	Average 65 lbs. per carton	Average 29.5 kg per carton
	Average 1.43 lbs. per tile	Average 0.65 kg per tile
BOXES PER PALLET	30	
STATIC LOAD LIMIT (MODIFIED ASTM F-970)	125 p.s.i	8.79 kg / cm ²
ASTM SPECIFICATION (F-1066)	Class II	
HUD / FHA REQUIREMENTS	Exceeds	
FLOORING RADIANT PANEL TEST (ASTM-E-648)	.45 watts / cm ² , Passes – Class 1	
FLAME SPREAD (ASTM E-84)	Passes	
N.B.S. SMOKE CHAMBER TEST (ASTM -E-662)	<450 Passes	
INSTALLATION ADHESIVE	Mannington V-11 / Full Spread, see pages 87-88	

- Color and pattern extend through the thickness of the tile.
- Meets the requirements of the Americans with Disabilities Act for static coefficient of friction as manufactured.
- Meets CHPS 01350 IAQ Test, passed and listed.
- VCT is not recommended for use in hospital operating suites, commercial kitchens, or in exterior areas that require static dissipation.
- Darker colors of vinyl composition tile may be subject to scratch whitening, requiring more frequent maintenance.
- Wood subfloors directly on concrete or sleepers—either on or below grade—are unsatisfactory for VCT installation.
- Dirt, wetness, and improper maintenance may cause significant variation in actual performance.
- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- Use door mats outside each entrance to prevent dirt, sand, grit, and other substances from being tracked onto the floor.

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.